


review of the international publication page 4, line 27. A markup sheet is enclosed illustrating the change as is a replacement page 7. The above amendment to the drawings is presented to correct a typographical error and the correction is apparent from review of the specification, since, for example, in the specification at page 8 line 8, it is noted that the resonance point appears at nearly 84 MHz.

The amendment to drawings is incorporated in a replacement sheet 4/8 of the drawings that is filed herewith.

Respectfully submitted,



James H. Walters, Reg. No. 35,731

802  
DELLETT AND WALTERS  
Suite 1101  
310 S.W. Fourth Avenue  
Portland, Oregon 97204 US  
(503) 224-0115  
DOCKET: A-411

09/980959

element is sufficiently separated from other conductive members, as shown in FIG. 4, as the frequency of an input signal becomes high, the forward gain becomes smaller. This is because the fact that the impedance of the inductor element having the predetermined inductance  $L$  is  $j\omega L$  and becomes large in proportion to the frequency of the input signal. JWL

On the other hand, as shown in FIG. 5, in the state that this inductor element is closely contacted to the copper plate, it is possible to maintain a high forward gain even if the input signal changes. This shows that this inductor element does not function as an original inductor since the inductance that this inductor element has becomes small by bringing the copper plate close to this inductor element. An estimated cause of decreasing the inductance is that eddy currents arise on the front side of the copper plate owing to magnetic flux, which is generated when a signal is inputted into the electrode, and cancel this magnetic flux.

In addition, in the measurement described above, although the copper plate was used as a substrate, even in the case that a semiconductor substrate is used instead of the copper plate, the same phenomenon happens fundamentally.

FIG. 6 is a graph showing the measurement result of the forward gain of an inductor element having two layers of electrodes that have the same shape and arrangement as the two conductors 1 and 2 included in the inductor element 10. In addition, FIG. 7 shows the forward gain of an inductor element having two layers of electrodes that have the same shape and arrangement as the two conductors 1 and 2 included in the inductor element 10, at the time of closely contacting a conductor substrate to this inductor element.

MARK UP 5/20

EXPRESS MAIL EL 89800333703